

PATLED[®]s

See more in more ways



CWF LED LIGHT BAR

Ideal for Workstations, Machine Lighting and Control Cabinets

- User-friendly Rocker Switch
- Several mounting bracket options
- Available lengths - 300mm, 600mm, 900mm



CLN LED SPOT LIGHT

Thin and Compact with High Intensity

- Water, oil, coolant resistant
- Tilt and pan-tilt bracket options
- Concentrated, focused light for general task lighting applications

CLK LED LIGHT BAR

Rugged Design; Built to Withstand Harsh Conditions

- High water, oil, chemical resistance; IP69k options
- Flexible body/lens options available
- M12 quick disconnect with Daisy Link compatibility
- Available lengths - 200mm, 300mm, 600mm



CWK LED LIGHT BAR

Compact and Durable with Broad Coverage

- Redesigned lens for wide-angled illuminance
- Oil resistant side cable
- Available lengths - 200mm, 300mm, 600mm

CLA LED LIGHT BAR

Ideal for High-pressure, High-temperature Washdown

- IP69k protection rating
- Diffusion lens type, great for vision systems
- Flexible mounting bracket options
- Available in 6 lengths - 100mm to 1200mm



ECOLAB[®]



CWA LED LIGHT BAR

Bright and Affordable

- Great as a fluorescent lighting replacement
- Clear lens type for brighter direct lighting
- Available lengths - 300mm, 600mm, 900mm



	CLK	CWK	CLA	CWA	CLN	CWF
PRIMARY APPLICATION	MACHINE TOOLING, EQUIPMENT LIGHTING, FOOD, MEDICINE, CHEMICAL	MACHINE TOOLING, EQUIPMENT LIGHTING	FOOD PROCESSING, BEVERAGE PROCESSING, PHARMACEUTICAL, PRINTING PRESS, AUTOMATION	COST EFFICIENT LIGHTING CONTROL PANEL LIGHTING ELEC. SYSTEM INTEGRATION PANEL SHOPS	MACHINE TOOLING, CONTROL PANEL, FOOD PROCESSING, BEVERAGE PROCESSING, PHARMACEUTICALS, ASSEMBLY LINES	CONTROL PANEL WORK STATION EQUIPMENT LIGHTING
EXTRA DESCRIPTION	FOCUSED LIGHT, ROBUST	WIDE DIFFUSED LIGHT, ROBUST	EMITS LOW HEAT, ENERGY EFFICIENT	EMITS LOW HEAT, ENERGY EFFICIENT	EXTREMELY THIN, 22.2MM WIDTH, WITH WIDE RANGE OF MOTION	WIDE DIFFUSED LIGHT
SIZES	200,300,600 MM	200,300,600 MM	100,200,300,600,900, 1200 MM	300,600,900 MM	85 MM	300,600,900* MM (*ONLY 100-240 VAC)
ENVIRONMENT RATING	IP66G/67G/69K	IP66G/67G	IP66/67/69K	IP65	IP66G/67G/69K	IP20
ENVIRONMENT	WATER AND OIL RESISTANT, CHEMICAL RESISTANT, HIGH TEMPERATURE, HIGH PRESSURE WASHDOWN	WATER AND OIL RESISTANT	HIGH TEMPERATURE, HIGH PRESSURE WASHDOWN	DUST TIGHT, PROTECTION AGAINST HEAVY SEAS	WATER AND OIL RESISTANT, CHEMICAL RESISTANT, HIGH TEMPERATURE, HIGH PRESSURE WASHDOWN	OPTIONAL MAGNETIC BRACKET FOR FLEXIBLE USAGE IN WORKSTATIONS OR CONTROL CABINETS
HOUSING	ALUMINUM ALLOY OR STAINLESS STEEL	ALUMINUM ALLOY	POLYCARBONATE RESIN	POLYCARBONATE RESIN	ALUMINUM ALLOY	ALUMINIUM ALLOY
WINDOW	TEMPERED OR ACRYLIC GLASS	TEMPERED GLASS	POLYCARBONATE RESIN	POLYCARBONATE RESIN	TEMPERED GLASS	POLYCARBONATE RESIN
CERTIFICATIONS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	UL, CUL, CE, ROHS	CE, ROHS, UL* (*ONLY 24 VDC)
VOLTAGE	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC, 100-240 VAC
OPERATING TEMPERATURE RANGE	-40°C TO 60°C	-10°C TO 50°C	-40°C TO 60°C	-30°C TO 60°C	-40°C TO 60°C	-25°C TO 60°C (24 VDC) -20°C TO 50°C (100-240 VAC)
MOUNTING OPTIONS	DIRECT, FLUSH AND SWIVEL WITH OPTIONAL BRACKET	DIRECT, FLUSH AND SWIVEL WITH OPTIONAL BRACKET	SCREW MOUNT, MAGNETIC MOUNT	SCREW MOUNT	DIRECT, PAN & TILT BRACKET	DIRECT, FLUSH AND SWIVEL WITH OPTIONAL BRACKET
LUMENS	865-2600 LM	800-2400 LM	60-1725 LM	350-1050 LM	550 LM	500-1500 LM
LIGHTING COLOR OPTIONS	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE	DAYLIGHT WHITE
LIGHTING TEMPERATURE	6500K	6500K	6800K	6500K	6500K	5700K
CABLE	SIDE EXITING, M12, DAISYLINK	SIDE EXITING	SIDE EXITING	SIDE EXITING	SIDE EXITING	SIDE EXITING
VIBRATION RESISTANCE	19.6 M/S ²	20 M/S ²	19.6 M/S ²	19.6 M/S ²	19.6 M/S ²	-

PATLITE[®]

PATLITE Europe GmbH
 Am Soeldnermoos 8, D-85399 Hallbergmoos, Germany
 TEL.+49 -811-9981-9770-0 FAX.+49-811-9981-9770-90
 E-mail: info@patlite.eu